

Adaptor Micro x 1/2" NPT Female

FITTINGS

Fittings

Micro Fittings, Adaptors, Nut and Tails

OPERATION

A range of micro fittings, adaptors, Nut and Tails for connecting to tubing, main water supply lines and emitters.


A 1/2" NPT Female adaptor for connection to 1/2" threaded risers with self-tapping micro connection for "*Fast*" Thread and 10-32 UNF male threaded micro emitters.

PRODUCT FEATURES

- Micro fittings and adaptors with barb or "FAST" thread connection.
- Nut and Tails (with Rotating Nut) for easy connection to tubing, main water supply lines and emitters.
- 1/2" NPT Female adaptor for connecting to 1/2" threaded risers.

GENERAL APPLICATIONS

• Landscaped gardens, green houses and vegetable gardens.



Adaptor "FAST" Thread x 4.5 mm Barb

4.5 mm Barb



Hypodermic Barb

Adaptor *"FAST"* Thread Winged





Elbow 4.5 mm Barb



Tee 4.5 mm Barb



3/4" BSP Female Nut x 4.5 mm Barb



3/4" BSP Female Nut x 13 mm Barb



4.5 mm Barb

		ELBOW	TEE	CROSS	JOINER		ADAP	NUT & TAILS			
PACKAGING		4.5 mm Barb				"FAST" Thread x 4.5 mm Barb	Hypodermic 4.5 mm Barb	"FAST" Thread Winged	Micro x 1/2" NPT Female	3/4" BSP Female Nut with Washer x 4.5 mm Barb	3/4" BSP Female Nut with Washer x 13 mm Barb
ORDER CODES	PACKS	100425	100445	100675	100406	100696	100706	100716	102094	203954	203964
	BULK	010042	010044	010067	010040	010069	010070	010071	010209	020395	020396
QUANTITY PER BAG	PACKS	50	50	50	100	100	100	100	25	25	25
	BULK	1000	1000	1000	1000	1000	1000	1000	500	1000	900
BAGS PER CARTON	PACKS	360	250	250	200	250	200	250	80	40	32
	BULK	28	18	12	24	28	25	26	5	1	1
WEIGHT PER CARTON (kg)	PACKS	14.0	12.5	15.0	14.6	14.3	14.2	15.0	8.8	7.4	10.6
	BULK	18.2	15.7	13.1	16.2	14.7	16.4	15.4	10.5	8.2	9.4
DIMENSIONS OF MICRO FITTINGS AND ADAPTORS	HEIGHT	19 mm	30 mm	30 mm	29 mm	27 mm	27 mm	27 mm	25 mm	33.5	49.0
	WIDTH	19 mm	19 mm	30 mm	10 mm	7.8 mm	16 mm	14 mm	27 mm	33.6	33.6
	DEPTH	7.4 mm	7.4 mm	7.4 mm	10 mm	7.8 mm	7.0 mm	7.7 mm	27 mm	33.6	33.6
	WEIGHT	0.6 g	0.8 g	1.0 g	0.6 g	0.5 g	0.6 g	0.5 g	3.7 g	7.2 g	11.9 g
MATERIAL UV STABILISED					Ac	Polypropylene	Acetal				

FITTINGS

Fittings

Rigid Risers, Ratchet Clamps, Repair Plugs, Micro Saddle and Accessories

OPERATION

Risers used to raise emitters above plant foliage. Ratchet Clamps for securing LDPE tube to barbed fittings. Micro Saddle for secure, leak free attachment to LDPE tube. *(Patented)* Repair Plugs for repairing holes in Low Density Polyetylene tubing. Pressure Reducer controls mains water pressure at the outlet to 180 kPa (1.8) Bar.

PRODUCT FEATURES

- Rigid Risers available in three lengths, 200 mm, 300 mm and 450 mm with barbed connection or "*FAST*" thread connection.
- The Micro Saddle provides secure, leak free attachment to LDPE tube. No tools required. Self Piercing for rapid installation. The 4.5 mm Barbed Take-Off adaptor provides connection for micro tube.

GENERAL APPLICATIONS

Rigid Riser with "FAST" Thread Adaptor

Rigid Riser with Barbed Adaptor • Landscaped gardens, greenhouses and vegetable gardens.





Micro Saddle OD16 - 18 with 4.5 mm Barbed Take-Off Adaptor



Repair Plugs (Rack of 10)



Ratchet Clamp OD16 - 18



Pressure Reducer

RIGID RISERS, RATCHET CLAMPS AND REPAIR PLUGS AND ACCESSORIES												
PACKAGING		RIGID RISERS with BARBED ADAPTORS			RIGID RISERS with <i>"FAST "</i> THREAD ADAPTORS			RATCHET CLAMPS		MICRO SADDLE	REPAIR PLUGS	PRESSURE REDUCER
		200 mm	300 mm	450 mm	200 mm	300 mm	450 mm	OD16 -18	OD19 - 21	OD16 -18 with 4.5 mm Barbed Take-Off Adaptor	4.5 mm Barb	3/4" BSP Female x 3/4" BSP Male
ORDER CODES	PACKS	200806	200816	200826	200836	200846	200856	101336	101356	104536	100802	202603
	BULK	020080	020081	020082	020083	020084	020085	010133	010135	010453	010080	020260
QUANTITY PER BAG	PACKS	100	100	100	100	100	100	100	100	100	10	20
	BULK	2300	1800	1100	2300	1800	1100	1000	1000	1000	500	500
BAGS PER CARTON	PACKS	23	18	11	23	18	11	65	50	40	200	25
	BULK	1	1	1	1	1	1	6	5	4	5	1
WEIGHT PER CARTON (kg)	PACKS	12.1	13.6	12.2	12.1	13.6	12.2	14.1	14.2	11.5	8.2	16.3
	BULK	12.0	13.4	12.1	12.0	13.4	12.1	12.8	14.0	11.3	8.5	16.1
Dimensions Of Fittings	HEIGHT	216 mm	316 mm	466 mm	217 mm	317 mm	467 mm	32 mm	36 mm	43 mm	49 mm	75 mm
	WIDTH	7.6 mm	7.6 mm	7.6 mm	14 mm	14 mm	14 mm	30 mm	35 mm	30 mm	28 mm	32 mm
	DEPTH	7.6 mm	7.6 mm	7.6 mm	7.7 mm	7.7 mm	7.7 mm	5.6 mm	6.6 mm	22 mm	8.5 mm	32 mm
	WEIGHT	4.8 g	6.9 g	10.2 g	4.8 g	6.9 g	10.2 g	2.0 g	2.8 g	3.5 g	3.0 g	30.4 g
MATERIAL UV STABILISED		HDPE						Acetal			Polypropylene	Polypropylene