

Stud Fittings

3675 Stud Fitting, Male BSPT Thread

	ØD	C		F1	F2	H	kg
4	R1/8	3675 04 10		10	3	15	0.009
	R1/4	3675 04 13		14	3	15	0.017
6	R1/8	3675 06 10		13	4	17	0.011
	R1/4	3675 06 13		14	4	17	0.018
8	R1/8	3675 08 10		15	5	19	0.015
	R1/4	3675 08 13		16	6	18	0.019
	R3/8	3675 08 17		17	6	18.5	0.027
10	R1/4	3675 10 13		18	7	23	0.026
	R3/8	3675 10 17		18	8	22.5	0.031
	R1/2	3675 10 21		22	8	22.5	0.056
12	R1/4	3675 12 13		20	7	25.5	0.033
	R3/8	3675 12 17		20	9	24	0.035
	R1/2	3675 12 21		22	10	23	0.051
14	R3/8	3675 14 17		22	9	27	0.042
	R1/2	3675 14 21		24	11	26	0.057

3601 Stud Fitting, Male BSPP and Metric Thread

	ØD	C		E	F1	F2	H	kg
4	M5x0.8	3601 04 19		3.5	10	2.5	15.5	0.006
	M6x1	3601 04 52		4.5	10	3	16	0.006
	M8x1	3601 04 56		5	11	3	14.5	0.007
	G1/8	3601 04 10		5.5	13	3	14.5	0.009
	G1/4	3601 04 13		6.5	16	3	14.5	0.015
6	M5x0.8	3601 06 19		3.5	13	2.5	19	0.010
	M10x1	3601 06 60		5.5	13	4	17.5	0.011
	G1/8	3601 06 10		5.5	13	4	17.5	0.011
	G1/4	3601 06 13		6.5	16	4	17	0.015
8	G1/8	3601 08 10		5.5	16	5	20	0.014
	G1/4	3601 08 13		6.5	16	6	18	0.016
	G3/8	3601 08 17		7.5	20	6	19	0.028
	G1/4	3601 10 13		6.5	18	7	25	0.025
10	G3/8	3601 10 17		7.5	20	8	22.5	0.028
	G1/2	3601 10 21		9	24	8	22.5	0.043
	G1/4	3601 12 13		6.5	20	7	26.5	0.030
12	G3/8	3601 12 17		7.5	20	9	26	0.034
	G1/2	3601 12 21		9	24	10	23.5	0.042
14	G3/8	3601 14 17		7.5	22	9	28	0.038
	G1/2	3601 14 21		9	24	11	26.5	0.045

3681 Stud Fitting with Internal Hexagon, Male Metric Thread

	ØD	C		E	F	G	H	kg
4	M5x0.8	3681 04 19		3.5	2.5	10	16	0.005

Related Products

- Polyurethane Tubing
- Polyamide Tubing
- Polyethylene Tubing
- Fluoropolymer Tubing
- Anti-Spark Tubing
- Fireproof PA Tubing
- Brass Flow Control Regulators