



European Profile

25, 26 and 27 Series



9101


Coupler, Male BSPP Thread

	Nickel-plated brass, NBR		DN	C		E	F	G	L	kg
7.2				G1/8	9101 26 10	9	22	27	43	0.073
				G1/4	9101 26 13	9	22	27	43	0.073
				G3/8	9101 26 17	9	22	27	13	0.075
				G1/2	9101 26 21	12	22	27	46	0.087

26 Series (DN 7.2): single shut-off = 1000 NI/min

9201


Coupler, Male BSPP Thread

	Nickel-plated brass, NBR		DN	C		E	F	G	L	kg
7.4				G1/4	9201 25 13	9	19	23	57	0.095
				G3/8	9201 25 17	9	19	23	57	0.097
				G1/2	9201 25 21	12	22	23	60	0.135
10				G3/8	9201 27 17	9	24	27	65	0.160
				G1/2	9201 27 21	12	24	27	70	0.166
				G3/4	9201 27 27	16	27	27	74	0.239

25 Series (DN 7.4): single shut-off = 1800 NI/min / 25 Series (DN 7.4): double shut-off = 710 NL/min
27 Series (DN 10): single shut-off = 2400 NI/min / 27 Series (DN 7.4): double shut-off = 900 NL/min

9214


Coupler, Female BSPP Thread

	Nickel-plated brass, NBR		DN	C		E	F	G	L	kg
7.4				G1/4	9214 25 13	9	19	23	55	0.098
				G3/8	9214 25 17	9	19	23	55	0.092
				G1/2	9214 25 21	12	24	23	57	0.124
10				G3/8	9214 27 17	12	24	27	68	0.177
				G1/2	9214 27 21	12	24	27	68	0.166
				G3/4	9214 27 27	16	32	27	74	0.255

25 Series (DN 7.4): single shut-off = 1800 NI/min / 25 Series (DN 7.4): double shut-off = 710 NL/min
27 Series (DN 10): single shut-off = 2400 NI/min / 27 Series (DN 7.4): double shut-off = 900 NL/min

9114


Coupler, Female BSPP Thread

	Nickel-plated brass, NBR		DN	C		E	F	G	L	kg
7.2				G1/4	9114 26 13	9	22	27	43	0.089
				G3/8	9114 26 17	9	22	27	43	0.084
				G1/2	9114 26 21	12	24	27	46	0.090

26 Series (DN 7.2): single shut-off = 1000 NI/min

9223

Coupler with Barb Connection

	Nickel-plated brass, NBR		DN	ØD		F	G	L	L1	kg
7.4				6	9223 25 06	19	23	73	25	0.095
				8	9223 25 08	19	23	73	25	0.097
				10	9223 25 10	19	23	73	25	0.097
				13	9223 25 13	19	23	73	25	0.099
10				8	9223 27 08	24	27	80	21	0.146
				10	9223 27 10	24	27	80	21	0.162
				13	9223 27 13	24	27	80	21	0.164
				19	9223 27 19	24	27	80	21	0.168

25 Series (DN 7.4): single shut-off = 1800 NI/min / 25 Series (DN 7.4): double shut-off = 710 NL/min
27 Series (DN 10): single shut-off = 2400 NI/min / 27 Series (DN 7.4): double shut-off = 900 NL/min