

## CleanAIR® Chemical 2F Asbest

Powered air purifying respirator



### Description

The battery-powered air purifying respirator (PAPR), the breathing protective device for increasing comfort and safety when combined with approved headtops.

### Application

The high performance respiratory protection system for environments contaminated by asbestos fibres.

# TECHNICAL DATASHEET

## CleanAIR® Chemical 2F Asbest

Powered air purifying respirator



### Technical specification

Product code	51 00 00ASD		
Flow rate	Airflow [lpm]	Mode	Filter category
	160 / 185 / 210 / 235	Mask	Particle
	160 / 185 / 210	EN 12942	Light combined (class 1)
Battery	Standard battery	Heavy Duty battery	
Voltage	14,4 V	14,4 V	
Capacity	2,6 Ah	5,2 Ah	
Charging time	< 3 hours	< 6 hours	
Operation time*	< 10 hour*	< 20 hours*	
Battery lifespan	up to 500 charging cycles	up to 500 charging cycles	
Battery charger	Microprocessor controlled, fully automatic Input: 100 - 240 V (50/60 Hz) Output: 18 V (max. 1 500 mA) Available plugs: EUR, UK and AUS		
Weight	1 000 g (incl. standard battery, excl. filters)		
Dimensions	235 mm / 126 mm / 65 mm (with standard battery)		
Noisiness	< 70 dB		
Materials	Unit: high performance polyamide Belt: Hypalon - synthetic rubber		
Motor	Ball-bearing brushless motor		
Input / Output (threads)	Filter thread - RD40x1/7" - 2x Airflow output thread - CA40x1/7" - 1x		
Belt - waist size:	Decontaminable Hypalon belt - up to 1 500 mm		
Standard Protection class / NPF**	EN 12941 TH3 / 500	EN 12942 TM3 / 2000	
Ingress protection	IP64: When switched ON (without any further requirements) IP65: When switched ON (set of spark arresters and pre-filter holders - 50 01 12) IP68: When switched OFF (with plugged inputs and output - 51 00 46)		
Display	TFT display (262k colours, 160x160 px) (showing actual working mode, airflow, filter condition and battery status)		
Storage conditions	- 10°C to + 55°C, humidity 20 - 95 % Rh		
Operating conditions	0°C to + 60°C, humidity 20 - 95 % Rh		

\* with new P3 filters and fully charged battery / \*\* depends on used headtop

### Disclaimer Notice

All the information contained herein is believed to be accurate and is subject to change without notice. Users should independently evaluate the suitability of each product for their own applications. CleanAIR® products are not designed for, and may not be used in, all applications.

# TECHNICAL DATASHEET

## CleanAIR® Chemical 2F Asbest

Powered air purifying respirator



### Product sets / variations

51 00 00ASD CleanAIR® Chemical 2F Asbest incl. decontaminable Hypalon belt, Li-Ion battery, charger, flow indicator (w/o hose)

51 00 00ASR CleanAIR® Chemical 2F Asbest incl. decontaminable rubber belt, Li-Ion battery, charger, flow indicator (w/o hose)

\* Add U or AUS to the end of product code for ordering charger with UK or AUS plug

### Spare parts and accessories

51 00 10 Standard battery Li-Ion 14,4 V / 2,6 Ah

51 00 20 Heavy Duty battery Li-Ion 14,4 V / 5,2 Ah

51 00 41 Decontaminable belt

51 00 42 Decontaminable harness

71 00 60 Light flexi hose QuickLOCK™ - CA40x1/7"

71 00 86 Rubber hose QuickLOCK™ - CA40x1/7"

71 00 62F Hose cover flameproof

70 00 62C Hose cover chemical resistant

51 00 30EUR Charger Li-Ion 14,4 V - EURO

51 00 30UK Charger Li-Ion 14,4 V - UK

51 00 30AUS Charger Li-Ion 14,4 V - AUS

51 00 46 Set of plugs (2x external thread, 1x internal thread) for decontamination of unit 2F

52 01 01 TFT display protective foil

### Technical features

**Warning system** - visual and audible warning for low airflow and low battery charge..

**Flow control system** - maintains level of airflow constant regardless filter clogging or battery charge.

**Automatic closing system** - reduces the risk of unwanted contamination of the unit while the filters are being changed

**Allows immersion disinfection** - with input and output threads plugs on (Sodium hypochloride or Persteril).

**LED display** - LED display visualises airflow, filter clogging and battery charge.

### Disclaimer Notice

All the information contained herein is believed to be accurate and is subject to change without notice. Users should independently evaluate the suitability of each product for their own applications. CleanAIR® products are not designed for, and may not be used in, all applications.

# TECHNICAL DATASHEET

## CleanAIR® Chemical 2F Asbest

Powered air purifying respirator



### Compatible headtops

72 01 02B	Short protective hood CA-1, blue	TH3
72 01 02	Short protective hood CA-1, orange	TH3
72 01 12	Short protective hood CA-1+, orange	TH3
72 01 12B	Short protective hood CA-1+, blue	TH3
72 02 02B	Long protective hood CA-2, blue	TH3
72 02 02	Long protective hood CA-2, orange	TH3
72 10 02	Chem-proof protective hood CA-10	TH3
72 03 00.01	Protective face shield UniMask, grey	TH3
72 03 00.02	Protective face shield UniMask, blue	TH3
72 03 00.03	Protective face shield UniMask, orange	TH3
72 03 00.04	Protective face shield UniMask, red	TH3
72 03 00.08	Protective face shield UniMask, neoprene	TH3
71 03 00	Grinding shield CA-3 (polycarbonate visor)	TH2
71 03 01	Grinding shield CA-3 (acetate visor)	TH2
71 04 01*	Safety helmet CA-4 orange face seal	TH2
71 04 03*	Safety helmet CA-4 additional flip-up visor, earmuffs, orange face seal	TH2
70 40 01	Safety helmet CA-40 weld. shield, ADF V9-13 DS	TH3
70 41 00	Safety helmet CA-40G grinding shield	TH3
70 42 01	Safety helmet CA-40GW grinding + welding shield, ADF V9-13 DS	TH3
70 20 70	Welding hood CA-20 ADF V9-13 DS	TH3
70 20 81	Welding hood CA-20 ADF V6-8/9-13 GDS	TH3
70 29 01	Welding hood CA-29 Evolve ADF V9-13 DS	TH2
70 05 00	Half mask CA-5 Eurmask DIN	TM2
71 06 00	Full face mask GX02, size [S, M, L]	TM3
72 06 00	Full face mask CF02, size [M, L]	TM3

\* for ordering blue face seal please add „B“ at the end of the product code

### Disclaimer Notice

All the information contained herein is believed to be accurate and is subject to change without notice. Users should independently evaluate the suitability of each product for their own applications. CleanAIR® products are not designed for, and may not be used in, all applications.

# TECHNICAL DATASHEET

## CleanAIR® Chemical 2F plus

Powered air purifying respirator



### Compatible filters

Product code:	Product name	P-white	A-brown	AX-brown	B-grey	E-yellow	K-green	Hg-red	Ozone (10 ppm)	EN 14387	EN 143	EN 12941	EN 12942	EN 148-1 (RD40x1/7")	Note:
<b>Combined filters, thread RD40*1/7"</b>															
50 03 57	A1P3	✓	✓									✓	✓	✓	-
50 01 57	A2P3	✓	✓							✓		✓	✓	✓	-
50 01 62	B2P3	✓			✓				✓	✓		✓	✓	✓	-
50 01 60	K2P3	✓					✓		✓	✓		✓	✓	✓	-
50 01 67	A2B2P3	✓	✓		✓				✓	✓		✓	✓	✓	-
50 01 64	A2B2E2P3	✓	✓		✓	✓			✓	✓		✓	✓	✓	-
50 03 64	A1B1E1P3	✓	✓		✓	✓						✓	✓	✓	-
50 01 68	A2B2E2K2P3	✓	✓		✓	✓	✓		✓	✓		✓	✓	✓	-
50 01 65X	NBC - A2B2E2K2P3	✓	✓		✓	✓	✓			✓		✓	✓	✓	NBC filtr
50 01 66	A2B2E2K2HgP3	✓	✓		✓	✓	✓	✓	✓	✓		✓	✓	✓	max. 50 hours
50 02 57	A2P - ZERO	✓	✓							✓		✓	✓	✓	two-thread filter
50 02 66	A2B2E2K2HgP - ZERO	✓	✓		✓	✓	✓	✓	✓	✓		✓	✓	✓	two-thread filter
50 02 68	A2B2E2K2P - ZERO	✓	✓		✓	✓	✓		✓	✓		✓	✓	✓	two-thread filter
<b>Particle filters, thread RD40*1/7"</b>															
50 00 48	P3	✓									✓	✓	✓	✓	-
50 02 49	ZERO	✓									✓	✓	✓	✓	two-thread filter
50 40 48	P3 lite	✓									✓	✓	✓	✓	-
50 42 49	ZERO lite	✓									✓	✓	✓	✓	two-thread filter

### Disclaimer Notice

All the information contained herein is believed to be accurate and is subject to change without notice. Users should independently evaluate the suitability of each product for their own applications. CleanAIR® products are not designed for, and may not be used in, all applications.