

EVOGuard®C4-MAX Industriel

EVOGuard® C4-MAX Industriel / ADA270-070-000



DESCRIPTION

Les écrans EVOGuard®C offrent une couverture faciale complète sans limiter les mouvements. L'écran de classe optique 1 offre une vision panoramique avec une déformation minimale.

Fully compatible with EVOGuard® browguard systems and *EVO® helmet models, the C4-MAX visor offers up to AT rated impact protection and features an integral chinguard for added coverage.

*Excluding EVO®6100 range.

OPTIONS

EVOGuard® C4-MAX Industriel (ADA270-070-000)

Écran EVOGuard® C4-MAX –Compatible avec EVO® VISTA® (ADA270-070-00C)

NORMES

EN 166 • EN 170



INFORMATIONS TECHNIQUES



RADIATION PROTECTION BREAKDOWN filtering effect
Scale Number
2C



LIGHT TRANSMISSION BREAKDOWN Lens Shade number
1,2



Manufacturer's Trademark
JSP Dagger



Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)
1



High Energy Impact resists a 6 mm, 0.86g ball @ 190 m/s
Maximum protection for face shields
A - lorsqu'il est monté sur un casque EVO®



Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum protection for goggles.
B Lorsqu'il est monté sur un serre-tête EVOGuard®



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional
T



Protection from Liquid Splash
3



Resistance to Molten Metals and Hot Solids Helmets (optional)
9



Resistance to Surface Damage by Fine Particles (optional)
K



Resistance to fogging (optional)
N



Visor Length
21.5 cm



BSI Kitemark
Oui



Material
Visière en polycarbonate



Product Weight
220g



Recyclable
Oui



Kit
Livré avec trois types d'accroches : pour EVO 2,3,5,DS, Lite, Skyworker. Pour casque avec EVOLite porte badge et EVO8 Systeme de serre-tête EVOGuard®

Lens Thickness - edge
1.70mm

Lens Thickness - centre
2.00mm

CARACTÉRISTIQUES



Compatibilité

La gamme EVOGuard® a été spécialement conçue pour être compatible avec des demi-masques, des masques, des lunettes de vue ainsi que les coquilles anti-bruit pour casque Sonis®.



Vision

L'écran de classe optique 1 offre une vision panoramique avec une déformation minimale, idéal pour une utilisation confortable toute la journée.



Impact

Wide range of high performance visors offering up to A rated impact resistance when fitted to a safety helmet and medium energy impact protection with the EVOGuard® browguard.



Couverture

Les écrans EVOGuard® offrent une couverture faciale complète sans limiter les mouvements. Les écrans EVOGuard® MAX offrent une excellente couverture grâce au retour menton intégral.



Protection UV

La visière filtre les rayons UV nocifs pour protéger les yeux tout en offrant une haute transmission de la lumière et une meilleure reconnaissance des couleurs.



Helmet & Browguard Integration

Compatible with EVO® helmet models and EVOGuard® browguard systems. Visor supplied with dual system clips for mounting to a helmet or browguard.



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jgpsafety.com / Web: www.jgpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jgpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 12 Mar 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.





 www.youtube.com/watch?v=_VnTgBRRT9E

TÉLÉCHARGEMENTS

 [Pack d'images \(ZIP\)](#)

 [doc-evoguard.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 3 / Issued 12 Mar 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

