

Raccords

L'usage de résine anaérobie pour réaliser l'étanchéité des assemblages vissés est interdit.

TES RÉDUITS 90°

> FEMELLE (Ø) - PIQUAGE - FEMELLE (ØR)

	Ø/ØR	Cond.	Réf.	€ HT		Ø/ØR	Cond.	Réf.	€ HT
 BTR50/25	20/16	S15*	BTR20/16	2,59	 BTR12/90	75/40	1	BTR75/40	35,18
	25/16	S10*	BTR25/16	3,19		75/50	1	BTR75/50	35,18
	25/20	S10*	BTR25/20	3,19		75/63	1	BTR75/63	35,18
	32/16	S10*	BTR32/16	4,23		90/25	1	BTR90/25	61,05
	32/20	S10*	BTR32/20	4,23		90/32	1	BTR90/32	61,05
	32/25	S10*	BTR32/25	4,23		90/40	1	BTR90/40	60,95
	40/16	S10*	BTR40/16	6,49		90/50	1	BTR90/50	60,95
	40/20	S10*	BTR40/20	6,49		90/63	1	BTR90/63	60,95
	40/25	S10*	BTR40/25	6,49		90/75	1	BTR90/75	60,95
	40/32	S10*	BTR40/32	6,49		110/25	1	BTR11/25	82,28
	50/20	S5*	BTR50/20	8,97		110/32	1	BTR11/32	82,28
	50/25	S5*	BTR50/25	8,97		110/40	1	BTR11/40	82,28
	50/32	S5*	BTR50/32	8,97		110/50	1	BTR11/50	82,28
	50/40	S5*	BTR50/40	8,97		110/63	1	BTR11/63	82,28
	63/20	1	BTR63/20	18,19		110/75	1	BTR11/75	82,28
	63/25	1	BTR63/25	18,19		110/90	1	BTR11/90	82,28
	63/32	1	BTR63/32	18,19		125/50	1	BTR12/50	130,75
	63/40	1	BTR63/40	18,19		125/63	1	BTR12/63	130,75
	63/50	1	BTR63/50	18,19		125/75	1	BTR12/75	130,75
	75/20	1	BTR75/20	35,18		125/90	1	BTR12/90	130,75
	75/25	1	BTR75/25	35,18		125/110	1	BTR12/11	130,75
	75/32	1	BTR75/32	35,18					

TÉS SIMPLES 90°

> FEMELLE/FEMELLE

	Ø	Cond.*	Réf.	€ HT		Ø	Cond.	Réf.	€ HT
 BTE20	16	S15	BTE16*	2,85	 BTE160	75	1	BTE75*	22,66
	20	S15	BTE20*	2,45		90	1	BTE90*	49,18
	25	S10	BTE25*	2,09		110	1	BTE110*	67,97
	32	S10	BTE32*	2,86		125	1	BTE125*	106,96
	40	S10	BTE40*	4,35		140	1	BTE140*	152,97
	50	S10	BTE50*	5,52		160	1	BTE160*	163,79
	63	S5	BTE63*	11,89		200	1	BTE200	399,18

TÉS À INSERT LAITON TARAUDÉS 90°

> FEMELLE/FEMELLE - G À VISSER

	Ø x G	Cond.	Réf.	€ HT		Ø x G	Cond.	Réf.	€ HT
 BTGRL4012	32 x 1/2"	1	BTGRL3212	43,97	 BTGRL	32 x 3/4"	1	BTGRL3234	58,04
	40 x 1/2"	1	BTGRL4012	46,51		40 x 3/4"	1	BTGRL4034	60,50
	50 x 1/2"	1	BTGRL5012	53,70		50 x 3/4"	1	BTGRL5034	69,01
	63 x 1/2"	1	BTGRL6312	64,76		63 x 3/4"	1	BTGRL6334	80,06

TÉS SIMPLES 90°

> FEMELLE/FEMELLE

	Ø	Cond.	Réf.	€ HT		Ø	Cond.	Réf.	€ HT
 BYT32	32	1	BYT32	11,22	 BYT32	50	1	BYT50	20,43
	40	1	BYT40	16,39		63	1	BYT63	30,69